



Cordless Flashlight ML006G / DML816



XGT
40V LITHIUM-ION
max

18V
LITHIUM-ION



**Max luminous flux:
500 lm**



ML006G

XGT
40V LITHIUM-ION
max

DML816

18V
LITHIUM-ION

**Continuous run time (approx)
on a full battery charge**

ML006G

51 h

Battery: BL4025
Low mode

DML816

75 h

Battery: BL1860B
Low mode



Max luminous flux
500 lm

Rotatable and foldable light head



Foldable light head

Rotatable light head
(90° right and 180° left)



Can be used as a compact stationary lamp with the light head swivelled and folded fully.

ML006G



DML816



Light diffusing lens

- softens the light of LED to reduce glare.
- provides widespread illumination.



Large hook

Light head is rotatable with the flashlight hanging down.



Retractable back into the upper portion of handle

Battery capacity warning

This system warns user by reducing the number of ON LED lights down to 1 before the battery is empty.

3-stage brightness adjustment

High → Medium → Low → OFF

Accessories

Lamp shade

Part No. GM00001326

By attaching to the Cordless Flashlight ML006G / DML816, the irradiation range is widened and the glare of the light source is reduced.



without Lamp shade

with Lamp shade

The light reaches the back

Charging Time

Flashlight Model	Fast Charging		Flashlight Model	Fast Charging	
	DC40RA	DC40RC		DC18RC	DC18SD
BL4020 2.0Ah 191L29-0	22 min	30 min	BL1815N 1.5Ah 196449-1	15 min	30 min
BL4025 2.5Ah 191B36-3	28 min	38 min	BL1820B 2.0Ah 197254-9	24 min	45 min
BL4040 4.0Ah 191B26-6	45 min	67 min	BL1830B 3.0Ah 197599-5	22 min	60 min
BL4050F 5.0Ah 191L47-8	50 min	85 min	BL1850B 5.0Ah 197280-8	45 min	110 min
			BL1860B 6.0Ah 197422-4	55 min	130 min

Cordless Flashlight

ML006G / DML816

	ML006G	DML816
Run Time (hrs)	Up to: 82 (Low mode, with BL4040)	Up to: 75 (Low mode, with BL1860B)
Illuminance (at 0.5m from the light source)	High/ Medium/ Low:	High/ Medium/ Low:
	800 / 400 / 180 lx	800 / 400 / 180 lx
Luminous Flux	High/ Medium/ Low:	High/ Medium/ Low:
	500 / 250 / 100 lm	500 / 250 / 100 lm
Dimensions (L x W x H)	w/ BL4040:	w/ BL1830B / BL1850B / BL1860B:
	275 - 408 x 85 x 148 mm (10-7/8 - 16 x 3-3/8 x 5-7/8")	267 - 400 x 79 x 127 mm (10-1/2 - 15-3/4 x 3-1/8 x 5")
Net weight	1.1 - 1.7 kg (2.4 - 3.8 lbs.)	0.70 - 1.1 kg (1.5 - 2.4 lbs.)

Standard Equipment : Shoulder hook set, Lamp shade

not covered by EPTA-Procedure
Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



Facebook MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE